

PC1 - Pressure table

09/2015

Nokian C-tyres															MM 09/2015
Axleload / axel (kg)															
Size	LI			300 kPa	325 kPa	350 kPa	375 kPa	400 kPa	425 kPa	450 kPa	475 kPa	500 kPa	525 kPa	550 kPa	575 kPa
175/65 R14	C	90	Y	1030	1080	1140	1200								
		88	P	1930	2030	2130	2240								
175/70R14	C	95	Y	1190	1250	1310	1380								
		93	P	2250	2360	2480	2600								
185 R 14	C	102	Y	1200	1290	1390	1460	1540	1620	1700					
		100	P	2280	2420	2560	2730	2900	3050	3200					
195 R 14	C	106	Y	1370	1460	1550	1640	1720	1810	1900					
		104	P	2600	2770	2940	3110	3270	3430	3600					
205 R 14	C	109	Y	1480	1580	1680	1780	1870	1960	2060					
		107	P	2810	3000	3180	3370	3540	3720	3900					
215 R 14	C	112	Y	1610	1720	1830	1930	2030	2130	2240					
		110	P	3060	3260	3460	3660	3850	4050	4240					
195/70 R15	C	104	Y	1300	1380	1470	1550	1630	1710	1800					
		102	P	2450	2620	2780	2930	3090	3240	3400					
205/70 R15	C	106	Y	1370	1460	1550	1640	1720	1810	1900					
		104	P	2600	2770	2940	3110	3270	3430	3600					
215/70 R15	C	109	Y	1488	1586	1634	1780	1874	1966	2060					
		107	P	2816	3004	3188	3368	3548	3724	3900					
225/70 R15	C	112	Y	1540	1670	1800	1910	2020	2130	2240					
		110	P	3040	3240	3440	3660	3880	4060	4240					
205/65 R15	C	102	Y	1400	1500	1600	1700								
		100	P	2600	2800	3000	3200								
215/65 R15	C	104	Y	1504	1604	1702	1800								
		102	P	2844	3032	3216	3400								
195/60 R16	C	99	Y	1296	1382	1466	1550								
		97	P	2440	2604	2760	2920								
215/60 R16	C	103	Y	1462	1560	1656	1750								
		101	P	2760	2940	3120	3300								
195/65 R16	C	104	Y	1280	1340	1410	1480	1550	1630	1710	1800				
		102	P	2440	2560	2680	2810	2950	3090	3240	3400				
185/75 R16	C	104	Y	1246	1328	1408	1488	1568	1646	1722	1800				
		102	P	2352	2508	2660	2812	2960	3108	3256	3400				
205/75 R16	C	113	Y	1418	1516	1614	1712	1810	1908	2006	2104	2202	2300		
		111	P	2668	2856	3044	3232	3420	3608	3796	3984	4172	4360		
205/65 R16	C	107	Y	1390	1460	1530	1610	1690	1770	1860	1950				
		105	P	2650	2780	2920	3060	3210	3370	3530	3700				
215/65 R16	C	109	Y	1470	1540	1620	1700	1780	1870	1960	2060				
		107	P	2800	2940	3080	3230	3390	3550	3720	3900				
225/65 R16	C	112	Y	1550	1652	1754	1854	1950	2048	2144	2240				
		110	P	2932	3128	3320	3508	3692	3876	4060	4240				

PC1 - Pressure table

09/2015

		Nokian C-tyres											MM 09/2015		
Axleload / axel (kg)															
Size		LI		300 kPa	325 kPa	350 kPa	375 kPa	400 kPa	425 kPa	450 kPa	475 kPa	500 kPa	525 kPa	550 kPa	575 kPa
235/65 R16	C	121	Y	1780	1870	1960	2060	2160	2270	2385	2490	2595	2695	2800	2900
		119	P	3370	3530	3700	3880	4070	4270	4470	4670	4865	5060	5250	5440
175 R 16	C	101	Y	1190	1270	1340	1420	1500	1570	1650					
		99	P	2240	2380	2530	2670	2820	2960	3100					
195/75 R16	C	107	Y	1350	1438	1526	1614	1698	1780	1866	1950				
		105	P	2560	2728	2896	3060	3224	3384	3540	3700				
225/75 R16	C	121	Y	1780	1870	1960	2060	2160	2270	2385	2490	2595	2695	2800	2900
		120	P	3350	3510	3680	3860	4050	4240	4440	4650	4870	5100	5340	5600
215/75 R16	C	116	Y	1660	1740	1830	1920	2010	2110	2208	2306	2404	2500		
		114	P	3140	3290	3450	3620	3796	3984	4172	4356	4536	4720		
205 R 16	C	110	Y	1530	1630	1730	1830	1920	2020	2120					
		108	P	2890	3080	3270	3450	3640	3820	4000					
215/60 R17	C	109	Y	1470	1540	1620	1700	1780	1870	1960	2060				
		107	P	2800	2940	3080	3230	3390	3550	3720	3900				
235/60 R17	C	117	Y	1590	1670	1750	1840	1930	2030	2130	2230	2340	2450	2570	
		115	P	3040	3190	3340	3500	3670	3850	4040	4230	4430	4640	4860	

PC1 - Pressure table

09/2015

Nokian Light Truck tyres										
Axleload / axel (kg)										
Size	LI / fitment		250	300	350	400	450	500	550	
			kPa	kPa	kPa	kPa	kPa	kPa	kPa	
LT215/85R16	115	Y	1390	1580	1760	1930	2120	2260	2430	
	112	P								
LT225/75R16	115	Y	1400	1590	1760	1940	2120	2280	2430	
	112	P								
LT235/85R16	120	Y	1580	1792	2000	2200	2380	2580	2760	
	116	P								
LT235/75R15	104	Y	1420	1620	1800					
	101	P								
LT245/75R16	120	Y	1580	1800	2000	2200	2380	2580	2760	
	116	P								
LT265/75R16	123	Y	1780	2020	2240	2480	2720	2880	3100	
	120	P								
LT285/75R16	122	Y	1980	2260	2500	2760	3000			
	119	P								
LT265/70R17	121	Y	1543	2000	2240	2440	2640	2780	2900	
	118	P								
LT315/70R17	121	Y	2300	2580	2900					
	118	P								
LT225/75R17	115	Y	1400	1590	1760	1940	2120	2280	2430	
	112	P								
LT235/80R17	120	Y	1600	1820	2060	2220	2430	2600	2800	
	117	P								
LT245/75R17	121	Y	1650	1870	2060	2280	2500	2680	2900	
	118	P								
LT245/70R17	119	Y	1570	1780	2000	2180	2360	2540	2720	
	116	P								
LT265/70R17	121	Y	1760	2000	2240	2440	2640	2780	2900	
	118	P								
LT285/70R17	121	Y	1960	2220	2500	2700	2900	2900	2900	
		P								
LT275/65R18	123	Y	1800	2040	2300	2500	2720	2920	3100	
	120	P								
LT275/70R18	125	Y	1920	2180	2430	2680	2900	3120	3300	
	122	P								
LT275/65R20	126	Y	1930	2200	2430	2680	2900	3080	3400	
	123	P								
31X10.5R15 LT	109	Y	1600	1800	2060					

1 bar = 100 kPa
1 lb/in² = 6,895 kPa

Y = Single fitment
P = Dual fitment